UNITED STATES PATENT AND TRADEMARK OFFICE CERTIFICATE OF CORRECTION

PATENT NO.

: 6,698,241 B1

Page 1 of 10

SCAN

PAGE

ATTACHED

APPLICATION NO.: 09/786668 : March 2, 2004

INVENTOR(S)

: Schwarzer

It is certified that error appears in the above-identified patent and that said Letters Patent is hereby corrected as shown below:

Formal drawings are attached to replace the informal drawings printed in the patent Column 10, line 36, change "press" to --pressing--

Delete the title page, showing an illustrative figure and substitute the attached title page.

Delete drawing sheet 1-8 and substitute the attached sheets containing figures 1-9.

This certificate supersedes certificate of amection issued January 8, 2008.

thighied and seemed this Fighth Daylof Upprafy 12008

Pieter State France State Color of S



(12) United States Patent

Schwarzer

(10) Patent No.:

US 6,698,241 B1

(45) Date of Patent:

Mar. 2, 2004

(54)	METHOD AN	D DEVICE FOR PRESSING A		
(75)	Inventor: Sleg	Slegfried Schwarzer, Stöckse (DE)		
(73)	Assignee: Her	Hermann Heye, Obernkirchen (DE)		
(*)	pate	ect to any disclaimer, the term of this nt is extended or adjusted under 35 C. 154(b) by 286 days.		
(21)	Appl. No.:	09/786,668		
(22)	PCT Filed:	Jul. 25, 2000		
(86)	PCT No.:	PCT/EP00/07088		
	§ 371 (c)(1), (2), (4) Date:	Mar. 8, 2001		
(87)	PCT Pub. No.:	WO01/09049		
	PCT Pub. Date:	Feb. 8, 2001		
(30)	Foreign A	pplication Priority Data		
		199 35 866		
(51)	Int. Cl. ⁷	C03B 11/06; C03B 11/16		
		65/29.12 ; 65/76; 65/79;		
(58)	Field of Search	65/158; 65/160; 65/229; 65/362 		
(56)	Re	eferences Cited		

U.S. PATENT DOCUMENTS

4/1890 Washington 65/177

1/1905 Marsh 65/209

5/1928 Pauwing et al. 65/229

6/1982 Northup 65/82

424,524 A

781,539 A

1,670,821 A

4,336,050 A

4,411,681 A

	LLÉ
	(57)
55 866 11/16 55/79; 5/362 19.18,	Met is co gob upper a pr An a and orificits I posi agai prel still pres which into fine a good and a good a

			•
4,662,923 A	٠	5/1987	Vajda et al 65/29.15
4,662,928 A	1	5/1987	Dauer 65/307
5,236,485 A	٠	8/1993	Leweringhaus et al 65/29.1
			Keller 65/158

FOREIGN PATENT DOCUMENTS

DE	32 32 288 C1	10/1983	C03B/9/193
EP	0 327 240 A1	8/1989	C03B/9/40
GB	2 178 421 A	2/1987	C03B/5/26


* cited by examiner


Primary Examiner—Sean Vincent
(74) Attorney, Agent, or Firm—Synnestvedt & Lechner
LLP

(57) ABSTRACT

thod and apparatus for pressing a parison. A parison mold emposed of neck tool halves and parison mold halves. A of molten glass had first been introduced through an er loading orifice into a cavity of the parison mold, while essing plunger was located in a lower loading position. assembly consisting of a pressing element, a guide sleeve a piston-cylinder unit was introduced into the loading ce. Subsequently the pressing plunger was raised from oading position into the illustrated upper end operating tion until its annular end face had moved into position nst a stop surface of the neck tool. Following the iminary pressing process a neck chamber in the cavity is free from molten glass. It is only at this point that the sing element exerts pressure on a base of the parison ch is being produced. The molten glass is also pressed the hitherto still free neck chamber of the cavity. The finish-pressing process of the parison is thus completed and the parison mold can be opened for the purpose of transferring the parison into a finish-forming station.

23 Claims, 8 Drawing Sheets






U.S. Patent


Sheet 2 of 8


Fig. 2






Sheet 3 of 8










Sheet 6 of 8





Sheet 7 of 8

Fig. 7




Fig.8

